

## SWIMMING POOL ABANDONMENT

### GRADING PERMIT REQUIREMENTS

- 1) CONTRACTOR/HOMEOWNER SHALL NEUTRALIZE THE EXISTING POOL WATER BEFORE DISCHARGING THE WATER INTO THE SEWER SYSTEM.
- 2) STOCKPILING MATERIAL IN THE STREET OR PUBLIC RIGHT-OF-WAY SHALL NOT BE ALLOWED.
- 3) DEMOLITION OF THE EXISTING POOL WILL NOT BE ALLOWED UNLESS THERE IS A FIVE (5) DAY FORECAST OF CLEAR WEATHER.
- 4) THE CONTRACTOR SHALL DEMOLISH A MINIMUM OF FOUR (4) FOOT OFF OF THE TOP OF THE EXISTING POOL.
- 5) ANY WALLS REMAINING BELOW THE FOUR (4) FOOT AREA SHALL HAVE HOLES PUNCHED THROUGH THE REMAINING WALLS WITH A JACKHAMMER AT 12 INCHES ON CENTER EACH WAY.
- 6) THE BOTTOM SHALL HAVE HOLES PUNCHED THROUGH THE BOTTOM AT 12 INCHES ON CENTER EACH WAY.
- 7) THE REMAINING HOLE SHALL BE BACKFILLED, WITH APPROVED NATIVE MATERIAL, IN 8-INCH LIFTS TO A RELATIVE COMPACTION OF 90%.
- 8) ANY OF THE EXISTING CURB, GUTTER AND SIDEWALK DAMAGED DURING THE WORK WILL BE REMOVED AND REPLACED AT THE CONTRACTOR/HOMEOWNERS EXPENSE.
- 9) THE PERMITTEE /CONTRACTOR SHALL NOTIFY THE CITY OF CONCORD ENGINEERING SERVICES TWO (2) BUSINESS DAYS PRIOR TO THE START OF ANY WORK.